

# REALTIME T401F FACE ID + FINGERPRINT + RFID BIOMETRIC TIME & ATTENDANCE RECORDER (Product Code : T401F)



## Realtime T401F

Face ID Based + Fingerprint + RFID + Password  
Based

Biometric Attendance Recorder

**RealTime T401F Face ID + FP + RFID + P/W Based Biometric T  
System**

**Authentication Modes: Face, FP, P/W, RFID, & Comb**

# with 1 year Manufacturer WARRANTY and Bill

Easy Installation

**No Expert Required**

High quality Branded Face id based Time Attendance Machine

**High quality easy to use Branded Time Attendance Software FREE!!**

Branded Product with 1 Year Manufacturer Warranty & Bill

## Realtime T401F Face ID with Finger Attendance Recorder

### Specifications

|                               |  |
|-------------------------------|--|
| Face template capacity        | 500  |
| Fingerprint template capacity | 5,000  |
| Attendance Log capacity       | 3,00,000 data                                  |
| Management log                | 10,000   |
| Card capacity                 | 5,000  |
| RFID card supported           | 125KHz EM/13.56MHz Mifare                      |
| Authentication modes          | Face/Fingerprint/Password/Card and combination |
| Identify Speed                | <1.0 second [1:N]                              |
| CPU'                          | ARM9 320MHz                                    |
| LED                           | 1 (Red-Green Dual Color)                       |
| Wiegand input                 | Inside and outside Wiegand (26/34)             |
| LCD display                   | 2.8 inch TFT color screen 320x240 pixel        |
| Interface/Comm.               | USB disk, TCP/IP, <b>WIFI (Charges Extra)</b>  |
| Audio output                  | Voice Interface                                |
| Language                      | English  |
| Power source                  | DC 12V/1.5A                                    |
| Battery backup                | <b>2 Hours Backup (Charges Extra)</b>          |
| Operating temperature         | 10°C - +60°C                                   |
| Operating humidity            | 20% - 80% RH                                   |

Note:

1) No warranty against physical damage / tempered / burn item

Battery(if added with the device).

2) Warranty does not include with Power supply adapter &

